

**Type IC, Air-Tight, Wet & Plenum Rated****DESCRIPTION**

4" Round Recessed LED With Integral
Driver In Connection Box
Commercial Grade Quality With Architectural Design


FEATURES & BENEFITS

2" Deep - Install Where Ceiling Space Is Limited
Single CCT 2700K, 3000K, 4000K, Dim to Warm or 5CCT options
CRI 90+ for True Color Rendering
Type IC Rated - No Housing Required - Save on Labour
Driver Inside Connection Box - No Junction Box Needed
Armored Cable & Metal Connectors - Open Plenum Rated

MOUNTING

Cut Hole In Ceiling And Snap Fixture In Opening With
Attached Spring Clips. Ceiling Clearance Required: 2"

DIMENSIONS: ID 4" OD 5" Cut Out 4" to 4 1/4"



120V TRIAC Dimmable Driver Included



Optional 120V-347V Driver 0-10V Dimmable



Order Separately as
[model # LLL-LD1535TR](#)

ORDERING GUIDE Example: **LL4RR - 30K - WH**

	CCT	Trim Finish	
LL4RR	- xxK	- xx	
2700K	27K	WH	White
3000K	30K	BK	Black
4000K	40K		
DTW 30K-18K	3018K	Dim to Warm 3000K to 1800K	
5CCT	5CCT	User Selectable 27-30-35-40-50K	

LL4RR**4" Round Regressed Open Plenum LED 14.5W**

Project:

Location:

Model #:

Qty:

Notes:

SPECIFICATION	
Applications	Recessed Ceiling Mount
Power	14.5 W
Single CCT Models (K)	2700 3000 4000 Dim to Warm 3000-1800K
Light Output White Trim (lm)	950 1000 1020 850
5 CCT Models (K)	2700 3000 3500 4000 5000
Light Output White Trim (lm)	860 910 960 990 960
Halogen Equivalent	90 W
Beam Angle	90°
CRI	90 +
Default Driver Input	120V AC Triac Dimmable
Optional Driver Input	120V-347V AC 0-10V Dimmable
Junction Box Wire Capacity	Max 5 No 12 AWG or 8 No 14 AWG
Power Factor	0.98
Approved Location	Insulated Ceilings, Open Plenum, Wet Locations
IP Rating	IP 54
Air Tight	Yes
Ambient Temperature	-40°F (-40°C) to +104°F (+40°C)
Projected Life	70% Light Output at 50,000 Hours
Certification	cULus
Warranty	10 Year Residential / 5 Year Commercial

AVAILABLE TRIMS

White



Black

ACCESSORIES

Sold Separately



Armored Low Voltage Extension FT6 / CMP rated
[10ft model # MEC10](#)



[13" Mounting Plate Flat model # MP4-2](#)



[13" Mounting Plate Flanged model # MP4](#)



[26" Long Flat Rough-In Plate model # RIP414](#)



[Flanged Plate with Hanger Bars model # FRP4](#)



[Goof Ring OD 5 3/4" model # GR4](#)



Emergency Back Up Drivers
for 0-10V drivers # [BLD-HM08D-YYY](#) - 0-10V dimmable
for triac drivers # [BLD-HM15D-YYY](#) - non-dimmable

Lotus LED Lights USA

250 H Street # 301, Blaine WA 98230 tel 360-200-5500
Hainesport NJ & Ferndale WA

www.LotusLEDLights.com

mailing addresses
warehouses

Lotus LED Lights CANADA

1080 Cliveden Ave # 6, Delta BC V3M 6G6 tel 604-538-3090
Delta BC & Mississauga ON