



Type IC, Wet, Air-Tight & Open Plenum

DESCRIPTION


4" Round Deep Regressed LED
3/8" Trim for High-End Contemporary Installations
Commercial Grade Quality Built To Last

FEATURES & BENEFITS

5 single CCT, Dim to Warm, & 5CCT field selectable options
3 1/2" Deep - Install Where Ceiling Space Is Limited
Armored Cable & Metal Connectors - Open Plenum Rated
Driver Inside Connection Box with Romex Quick Connectors
and Knock Outs - Fast Installation & No Junction Box Needed
Type IC, Air-Tight & Wet Location - No Housing Required

DIMENSIONS ID 3 3/4" OD 4 1/8"

Ceiling Clearance Required: 3 1/2" Cut Out 3 3/4"

ORDERING GUIDE Example **LD4R-30K-4R-WR-TT**

LD4R	CCT	Reflector - Trim	Beam Angle
	- xxK	- 4R-xR-TT	
2700K	27K	- 4R-WR-TT	ank for 30°
3000K	30K	- 4R-SR-TT	-15D 15°
3500K	35K	- 4R-BR-TT	-60D 60°
4000K	40K		
5000K	50K		
DTW 30-20K	32K	Dim To Warm 3000K to 2000K	
DTW 30-18K	3018K	Dim To Warm 3000K to 1800K	
5CCT	5CCT	User selectable 27-30-35-40-50K	



LD4R-TT

4" Thin Trim Round Deep Regressed LED 15W

Project:

Location:

Model #:

Qty:

Notes:

SPECIFICATION

Applications	Recessed Ceiling Mount Thin Trim	
Power	15W	
Color Temperature CCT (K)	2700 3000 3500 4000 5000 DTW 30-20K DTW 30-18K	
Light Output Single CCT (lm)	1380 1430 1400 1500 1460 1130 1300	
Light Output 5CCT (lm)	1170 1240 1350 1400 1420	
Beam Angle	30° (default), 15° & 60° optional	
CRI	90 +	
Default Driver Input	120V AC	Triac Dimmable
Optional Driver Input	120V-347V AC	0-10V Dimmable
Junction Box Wire Capacity	Max 5 No 12 AWG or 8 No 14 AWG	
Approved Location	Insulated Ceilings, Open Plenum, Wet Locations	
IP Rating	IP 54	
Air Tight	Yes	
Ambient Temperature	-40°F (-40°C) to +104°F (+40°C)	
Projected Life	70% Light Output at 50,000 Hours	
Certification	cULus	
Warranty	10 Year Residential / 5 Year Commercial	

AVAILABLE TRIMS



White Reflector
White Trim
4R-WR-TT



Silver Reflector
White Trim
4R-SR-TT



Black Reflector
Black Trim
4R-BR-TT

120V TRIAC Dimmable Driver Included

Optional 120V-347V

0-10V Dimmable

Order Separately as

[model # LLL-LD1535TR](#)

ACCESSORIES

Sold Separately

[26" Long Flat Rough-In Plate model # RIP334](#)[Armored Low Voltage Extension 10ft model # MEC10](#)

Emergency Back Up Drivers

[for 0-10V drivers # BLD-HM08D-YYY - 0-10V dimmable](#)[for triac drivers # BLD-HM15D-YYY - non-dimmable](#)

Lotus LED Lights USA

250 H Street # 301, Blaine WA 98230 tel 360-200-5500
Hainesport NJ & Ferndale WA

www.LotusLEDLights.com

mailing addresses
warehouses

Lotus LED Lights CANADA

1080 Cliveden Ave # 6, Delta BC V3M 6G6 tel 604-538-3090
Delta BC & Mississauga ON