



LB4R24V

4" Round 24V DC Economy Super Thin Recessed LED 11W



Type IC, Wet & Air-Tight

DESCRIPTION

4" Round 24V DC Constant Voltage Recessed LED
Fits Where No Other Recessed Fixture Can


FEATURES & BENEFITS

1/2" Deep - Install Directly Under Joists -
Maximum Layout Flexibility
Low voltage wiring
Fast & Easy To Install - Save On Labor
Type IC Rated - No Housing Required
Connect multiple fixtures to one driver:
up to 8 per a 96W power supply

MOUNTING

Cut Hole In Ceiling And Snap Fixture In Opening With Attached
Spring Clips. Ceiling Clearance Required : 1/2"

DIMENSIONS: ID 4" OD 4 7/8" Cut Out 4" to 4 1/4"



ORDERING GUIDE Example: LB4R24V/30K/WH

	CCT	Trim Finish	
LB4R24V	/	/	
2700K	27K	WH	White
3000K	30K	BK	Black
4100K	41K		

Driver is Not included

Project:

Location:

Model #:

Qty:

Notes:

SPECIFICATION

Applications	Recessed Ceiling, Showers & Soffits		
Power	11 W		
Colour Temperature	2700	3000	4100
Light Output	670	700	730
Halogen Equivalent	65 W		
Beam Angle	110°		
CRI	80		
Input Voltage	24V DC Constant Voltage		
Dimmability	To 5% With Compatible Driver & Dimmer		
Approved Location	Insulated Ceiling & Wet Locations		
IP Rating	IP 54		
Air Tight	Yes		
Ambient Temperature	-40°F (-40°C) to +104°F (+40°C)		
Projected Life	70% Light Output at 25,000 Hours		
Certification	cULus		
Warranty	3 Year		

AVAILABLE TRIMS



White



Black

ACCESSORIES

Sold Separately



[26" Long Flat Rough-In Plate model # RIP414](#)



[13" Long Flat Rough-In Plate model # MP4-2](#)



[13" Long Flanged Rough-In Plate model # MP4](#)



[4 1/8" Hole Flanged with Hanger Bars model # FRP4](#)



Goof Ring OD 5 3/4"

[White model # GR4](#) [Black model # GR4-BK](#)

Lotus LED Lights USA

250 H Street # 301, Blaine WA 98230 tel 360-200-5500
Hainesport NJ & Ferndale WA

www.LotusLEDLights.com

mailing addresses
warehouses

Lotus LED Lights CANADA

1080 Cliveden Ave # 6, Delta BC V3M 6G6 tel 604-538-3090
Delta BC & Mississauga ON