



SDD-24060-DIM

2 in 1 Driver + Dimmer for Single CCT LED 24V 60W

Project: _____

Location: _____

Qty: _____

Notes: _____

DESCRIPTION

Driver + Dimmer 2 in 1

Class 2 power supply for electrical box installation


Use with: [all single CCT / DTW LED tape](#)[all 24V DC fixtures](#) [24V pucks](#) [24V step lights](#)

FEATURES & BENEFITS


Eliminates compatibility issues between drivers and dimmers

Includes separation plate that allows installation of high and low voltage circuits in the same box

Fine tuning of the output voltage



SINGLE POLE WIRING




3-WAY WIRING DIAGRAM



ORDERING GUIDE

SDD-24060-DIM

SPECIFICATION	
Applications	24V DC single CCT & DTW LED installations
Power	60 W
Input	120V AC 60 Hz
Output V / A	24V DC / 2.5A
Voltage Adjustment	24 to 26 V +/- 0.5V
Type	Constant Voltage PWM output
Min / Max Load:	no minimum / 60 W
Dimming Range	0.3% - 100%
Wiring	Single Pole or 3-Way
THD	< 10% at full load
Power Factor	> 0.99 at full load
Efficiency	91% at full load
Inrush Current	50A, 150us @ 50%
Leakage current	< 0.5mA
PWM Frequency	16 KHz
Net Weight	0.55 lbs / 0.25 kg
Protection	short circuit, over-voltage, over-heat, over-load
Approved Location	Dry & Damp Locations
Working Temperature	-40°F (-40°C) to +140°F (+60°C)
Warranty	5 Year when used with Lotus products
Safety standards	c UL us Listed UL8750; CAN/CSA-C22.2 No.250.13
Certifications	Class 2, UL Class P, FCC Part 15 Subpart B Class B



Derating Curve (Output power VS Ambient TEMP)



Lotus LED Lights USA

250 H Street # 301, Blaine WA 98230 tel 360-200-5500
Hainesport NJ & Ferndale WA

www.LotusLEDLights.com

mailing addresses
warehouses

Lotus LED Lights CANADA

1080 Cliveden Ave # 6, Delta BC V3M 6G6 tel 604-538-3090
Delta BC & Mississauga ON