



LB4S-24V

4" Square 24V DC Super Thin Recessed LED 13W



Project:

Location:

Model #:

Qty:

Notes:

DESCRIPTION

4" Square 24V DC Input Recessed LED

Fits Where No Other Recessed Fixture Can

FEATURES & BENEFITS

1/2" Deep - Install Directly Under Joists, Maximum Layout Flexibility

No driver included - connect direct to 24V DC

Dimmable when connected to dimmable drivers



Connect up to 6 fixtures per a 96W power supply

MOUNTING

Cut Hole In Ceiling And Snap Fixture In Opening With Attached Spring Clips. Ceiling Clearance Required For Driver: 2 1/2"

DIMENSIONS: ID 4 1/8" OD 4 3/4"

Cut Out Round 4 1/8" to 4 1/4"



AVAILABLE TRIMS



White

ORDERING GUIDE

LB4S-24V-30K-WH

In stock only 3000K White Trim

Other CCT and trim colors available as custom order

SPECIFICATION	
Applications	Low Voltage Recessed
Energy Used	13 W
Colour Temperature	3000
Light Output	750
Halogen Equivalent	90 W
Beam Angle	110°
CRI	80
Input	24V DC
Dimmability	Constant Voltage Dimmable
Approved Location	Insulated Ceiling, Wet & Damp Locations
IP Rating	IP 54
Air Tight	Yes
Ambient Temperature	-40°F (-40°C) to +104°F (+40°C)
Projected Life	25,000 Hours
Certification	cULus
Warranty	3 year - when installed with a Lotus LED Lights Driver
	The warranty is void if installed with an LED driver from another manufacturer

ACCESSORIES

Sold Separately



[13" Mounting Plate Flat model # MP4-2](#)



[26" Long Flat Rough-In Plate model # RIP414](#)



[Flanged Plate with Hanger Bars model # FRP4](#)



[DRIVERS](#)

Lotus LED Lights USA

250 H Street # 301, Blaine WA 98230 tel 360-200-5500
Hainesport NJ & Ferndale WA

www.LotusLEDLights.com

mailing addresses
warehouses

Lotus LED Lights CANADA

1080 Cliveden Ave # 6, Delta BC V3M 6G6 tel 604-538-3090
Delta BC & Mississauga ON