

AD-107T

Ultra Slim LED Puck Light 2.2W

Project:

Location:

Qty:

Notes:

DESCRIPTION

Slim to size and bright in lumen output

With a width of 1/4", the puck light can be recess or surface mounted

Easily swap the trim color with the magnetic technology engineered into the pucks

White, Black and Brushed Nickel trims included or White trim only optional

White Surface Mount Bracket Included

Connect the puck lights to the power supply using a 6-port hub or /

and male and female connectors on every puck for daisy chaining

Puck lights can be purchased in single packs (with 3 trims or white trim only),

3 packs (3 trims with 12V power supply) or 10 packs (with white trim only)

FEATURES & BENEFITS


Fast & Easy to install - save on labor. CRI 90+ for true color rendering

DIMENSIONS ID 2 1/4" OD 3"




INSTALLATION

1/4" Thin Surface Mounted



1/8" Thin Recessed Mounted



CONNECTION

Puck Lights should be connected in parallel to the power supply.

Observe the power limitations. A 12W driver could power up to 5 pucks

ORDERING GUIDE

	CCT	Input Voltage	Packaging
AD-107T-3K	3000K	12 V DC	single - 3 trims
AD-107T-4K	4000K	12 V DC	single - 3 trims
AD-107T-3K-24V	3000K	24 V DC	single - 3 trims
AD-107T-4K-24V	4000K	24 V DC	single - 3 trims
AD-107T-3K-WH	3000K	12 V DC	single - WH trim only
3P-AD-107T-3K	3000K	12 V DC	3 pack - 3 trims
3P-AD-107T-4K	4000K	12 V DC	3 pack - 3 trims
10P-AD-107T-3K-WH-12V	3000K	12 V DC	10 pack - WH trim only
10P-AD-107T-4K-WH-12V	4000K	12 V DC	10 pack - WH trim only
10P-AD-107T-3K-WH-24V	3000K	24 V DC	10 pack - WH trim only
10P-AD-107T-4K-WH-24V	4000K	24 V DC	10 pack - WH trim only



SPECIFICATION	
Applications	Undercabinet, Cove, Hospitality, Retail Lighting
Energy Used	2.2 W
Color Temperature (K)	3000 4000
Light Output (lm)	150 170
Halogen Equivalent	15 W
Beam Angle	120°
CRI	90 +
Input	12 V DC / 24V DC
Dimming	Plug-in Driver not Dimmable
	Hard Wired Driver TRIAC Dimmable 10% - 100%
Approved Location	Damp Locations
Ambient Temperature	-4°F (-20°C) to +104°F (+40°C)
Projected Life	70% Light Output at 50,000 Hours
Certification	cETLus
Warranty	3 year - when installed with a Lotus LED Lights driver
	The warranty is void if installed with an LED driver from another manufacturer

Trim Options

White Surface Mount Bracket Included



White

Black

Brushed Nickel



White
Surface Mount Bracket

Optional **Wall Wash** (Eyelid) Trims - order as adder



WWT-WH-107



WWT-BK-107



WWT-BN-107

ACCESSORIES

Sold Separately



Hard Wired Driver Triac Dimmable Input 120V AC

[12V model # HBL024-120-12-D](#)

[24V model # HBL024-120-24-D](#)

Connect Up To 10 Puck Lights To This Driver

[Plug-In Driver model # WLS-PD30LU-24](#)

Not Dimmable Input 120V AC output 12V DC 12W

Connect Up To 5 Puck Lights To This Driver

6-Port Hub model # **AD-107THB1**

[Extension Cable 6 ft model # PEX6](#)

Surface Mount Brackets

Black model # **107BP-BK**, Brushed Nickel model # **107BP-BN**

Lotus LED Lights USA

250 H Street # 301, Blaine WA 98230 tel 360-200-5500
Hainesport NJ & Ferndale WA

www.LotusLEDLights.com

mailing addresses
warehouses

Lotus LED Lights CANADA

1080 Cliveden Ave # 6, Delta BC V3M 6G6 tel 604-538-3090
Delta BC & Mississauga ON